



NetDrive™

Easy and automatic LTO tape creation, review or restore. Use standalone or connect to network.



1 Beyond NetDrive™

Easy Archive to LTO Tapes

Connect hard drives or card readers directly to the NetDrive and drag and drop directly to tape. As easy to use as copying files to external hard drives.

Offload to LTO & Disk Concurrently

Comes with 1 Beyond Wrangler software which allows simultaneous copy from a source to multiple destinations in one step. Saves time when duplicate copies are needed.

Available with LTO-6 & LTO-7

Write speeds up to 280 MB/s on LTO-7 and 160 MB/s on LTO-6. Tower and Rack can support dual drives with LTO-5, LTO-6 and LTO-7 options.

Industry Standard LTFS Format

With LTFS, tapes made on the NetDrive can be read on Mac, PC or Linux platforms. Deliver to TV networks that now require LTFS formatted tapes.

No Computer Required

Unlike other tape drive solutions, NetDrive systems are all-in-one solutions. This frees up other computers for editing or other tasks.

Use Standalone or via Network

Backup directly from built-in card readers and external drives or connect via ethernet to a network so all computers (Mac or PC) in the office can archive.

NetDrive Models



NetDrive™ Portable

Rugged and small, the NetDrive Portable is ideal for on-set backup.



NetDrive™ Tower

NetDrive Tower is the most affordable and offers great flexibility.



NetDrive™ Rack

3U Rack Mount chassis maximizes performance and capability.

For more technical specs, please visit our website at www.1Beyond.com or contact us at sales@1beyond.com or (617) 591 -2200.

NetDrive™ Technical Specifications

	Portable	Tower	Rack
Standard Configuration	1 LTO-6 or LTO-7 Drive		
Customizable Openings	1 x 3.5"	2 x 5.25", 2 x 3.5"	1 x 5.25", 1 x 3.5"
Included Software	1 Beyond Wrangler Software & 1 Beyond Watch Folder		
Storage Capacity	3TB (LTO-6), 6TB (LTO-7)		
CPU	6th Generation Intel® Processor, 8 CPU		
RAM	8GB		
USB Inputs	5 x USB 3.0	6 x USB 3.0, 2 x USB 3.1	
Ethernet	2 x RJ-45 Gigabit		
Other Ports	1 x PS/2		
Power Consumption	~50W		
Operating Temperature	0°C~+35°C (32°F~+95°F)		
Storage Temperature	-20°C~+60°C (-4°F~+140°F)		
Storage Humidity	5-95% relative humidity		
Cooling	120mm cooling fan		
Power	115-230V AC , ~50W		
Dimensions	8.7" x 5.1" x 13.5"	16.5" x 7.8" x 16.8"	5.2" x 19" x 20.7"
Weight	12lbs	35lbs	45lbs

NetDrive™ Options

	Portable	Tower	Rack
5.25" Options			
Additional LTO Drive LTO-5, LTO-6, or LTO-7	-	√	√
SSD/HDD Array 4 x 1TB , 6 x 1TB	-	√	√
3.5" Options			
Multi-Card Reader CF, SD, etc	√	√	√
SSD/HDD Array 2 x 1TB	√	√	√
Other Options			
2 x 10GbE Connections	√	√	√
Upgrade to PRO 16GB RAM & 12CPU	-	√	√
Optional Software	Pre-Roll Post, CatDV, YoYotta, 1 Beyond EzLTOCat, 1 Beyond EzLTOList, EzPrep for Discovery		
External	Additional LTO Drives, USB Card Readers and Storage		

Visit our website at www.1Beyond.com or contact us at sales@1beyond.com or (617) 591-2200.

