

Hawk™

Dual Camera Tracking Solution

OVERVIEW

- **ENHANCE MEETINGS WITH SPEAKER TRACKING**

Simple, cost effective speaker tracking solution for small to medium size rooms where a close-up view of the meeting participants is desired. Everyone in the meeting has an equal look and feel.

- **PRODUCTION QUALITY MEETINGS**

Two HD PTZ cameras work together intelligently so that every time the Hawk™ quickly cuts to a new speaker, no camera movement is seen. 12x optical zoom provides consistent image quality.

- **AUDIO-LOCATING AND FACIAL DETECTION**

Built-In reference microphone and wide-angle camera combined with advanced image processing allow the Hawk to match the audio location with a face and automatically switch to a shot of the person speaking.

- **EASY SETUP AND CONFIGURATION**

Just add your favorite microphone and route the far end audio to the device for echo cancellation. After initial configuration the Hawk does not need to be connected to the network or a computer running specialized software.

- **CONTROL SYSTEM COMPATIBILITY**

VISCA compatibility ensures this camera system can be controlled from any popular control system including Crestron and Extron.

- **HARDWARE AND SOFTWARE CODEC COMPATIBILITY**

Up to 1080p60 video can be used with popular software codecs such as Zoom, Microsoft Teams, in addition to traditional hardware-based codecs.



FEATURES

- No Extra Equipment Needed
- AI Tracking Built Into Camera
- Conversation Following Switching

APPLICATIONS

- Small-Medium Conference Rooms
- Hybrid Classrooms
- Council Meeting Spaces
- Distance Learning
- Video Conferencing

SUPPLIED ACCESSORIES

- Power Supply
- Serial Control Breakout
- USB with 1B Cam Manager Software
- 3.5mm TRS Audio Cable
- Wall Shelf Mount

Hawk™

Dual Camera Tracking Solution



SPECIFICATIONS

Image Sensor-Tracking Cameras	1/2.8" Sony Exmor CMOS, 2.14MP
Image Sensor-Reference Cameras	1/3" CMOS
Signal Formats (HD)	1080p60/50/30/25, 1080i60/50, 720p60/50
Focal Length & Iris	f=3.9mm - 46.8mm, F1.6 - F2.8
Zoom	12X Optical, 12X Digital
Field of View	72.5° - 6.3° (PTZ Cameras), 86° (Wide-Angle Cameras)
Focus System	Auto, Manual, PTZ Push, One Push
Minimum Illumination	0.5 Lux (Color), 0.1 Lux (B/W)
Shutter Speed	1/25 - 1/10,000 sec
Gain	Auto, Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Track
Exposure	Auto, Manual, Shutter Priority, Iris Priority
S/N	≥50db
Tilt/Pan Angle	Tilt: -30° - +90°, Pan: 90° - 90°
Tilt/Pan Speed	Tilt: 0.1° - 80° /s, Pan: 0.1° - 120° /s
Number of Presets	Up to 256
Streaming Resolution	Up to 1080p60, User-selectable framesize/framerate/bitrate
IP Video Compression	H.265, H.264 (Four streams)
IP Audio Compression	AAC (IP Stream Only)
Protocol	HTTP, RTP, TCP, UDP, ONVIF
Streaming	RTSP, RTMP
Video Outputs	1x HDMI, 1x 3G-SDI (Tracking)
Audio Input/Output	2x Line In (one with echo cancellation), 1x Line Out
Network	1x RJ45, 10Mb/100Mb
USB	1x USB 2.0 (future)
Control	TCP/IP RS-232
Serial Control	PELCO-D, VISCA, PELCO-P
Power	DC12V, <24W
Operating Temperature	32° - 104° F (0° - 40° C)
Dimensions & Weight	19.69" x 6.4" x 5.71" (500mm x 163mm x 145mm), 6.61lbs (3KG)
Color	Gray
Mounts	3x 1/4" Threaded Mount Hole for 90° Wall Shelf Mount